

everywhere at home

AP Touch Panel PC 12,1",15",19" AP Touch Panel PC Wide 15,6", 18,5", 21,5"











AP-Touch Panel PC

AP-Touch Panel PC 12,1", 15", 19"



12,1" (30,48cm)| Art.-Nr. 04622 15" (31,80cm)| Art.-Nr. 04625 19" (48,26cm)| Art.-Nr. 04629

Due to their VESA socket AP-Touch Panels can be mounted fast and so are ready for use at once. The solid stainless steel chassis is carried out according to protection class IP 65. Regardless of this the built-in depth is just 6cm. The device works fanless and is equipped with a TFT LCD monitor. Examples for work assignment are shopping malls, DIY- markets and industrial halls. As operating system Windows® 7 Professional is preinstalled on 16 GB SSD drive.

Technical Data AP-Touch Panel PC

- Flat-panel PC with resistive touch screen
- Color TFT LCD
- Processor: Intel® Pineview Dual Core D525 1.8 GHz
- Measures WxHxD (in mm): 331 x 265 x 55 / 386 x 308 x 60 / 449 x 374 x 60
- Resolution: 1024 x 768 (12"/15")/ 1280 x 1024 (19")
- Backlight: 370/350/300 cd/m2
- Memory: 16 GB SSD
- Working Memory: 2GB (max. 4GB)
- Connections:
 - 1 x RJ-45 10/100/1000 Base-T Ethernet Port,
 - 1 x Mic-in, 1 x Line-out, 4 x USB-Port,
 - 4 x COM port RJ 45 (RS-232 x 3, RS-232/485 x 1),
 - 1 x Parallel Port, 1 x PCI express, 1 x mini-PCI,
 - 1 x 2.5" HDD Bay
- Speaker: 1 x 3 Watt (12")/ 2 x 3 Watt (15"/19")
- Power Supply: 12 V DC (included in delivery)
- Operation system: Windows® 7 Professional
- Control T preinstalled
- Front: stainless steel
- Optional: Mounting 100 x 100 mm VESA Standard



b.a.b-technologie gmbh Inhouse Dortmund Rosemeyerstraße 14 44139 Dortmund phone: +49 231 - 476 425 - 30 fax: +49 231 - 476 425 - 59 e-mail: info@bab-tec.de internet: www.bab-tec.de

AP-Touch Panel PC wide 15.3", 18.5", 21.5"



15,6" (39,62cm) | Art.-Nr. 04635w / 04635s 18,5" (46,90cm) | Art.-Nr. 04639w / 04639s 21,5" (54,61cm) | Art.-Nr. 04641w / 04641s

AP-Touch Panels wide captivate with their noble piano-finish look. The completely flat surface is framed within a massive metal chassis. Having a depth of just 48 mm the panels are extremely flat. The strait white or black coloured frame doesn't emerge when mounted on a wall. Regardless of the flat construction the surface complies with protection class IP 65.

The used display is a wide screen LED LCD which works with a true flat projected capacitive touch offering the ability of gesture control. An Intel® Pineview Dual Core (D525 with 1.8 GHz) e.g Intel® Celeron (G540 2,5 GHz) for 21,5" is used as processor. Examples for work assignment are check- in desks, salesrooms, hospitals but also the e-home.

Technical Data AP-Touch Panel PC wide

- Extreme flat-panel PC with true flat projected capacitive Color LED LCD
- Prozessor: Intel[®] Pineview Dual Core D525 1,8 GHz, Intel[®] Celeron G540 2,5 GHz (21,5")
- Measures WxHxD (in mm): 396 x 245 x 48 / 464 x 284 x 48 / 536 x 328 x 48
- Resolution: 1366 x 768 (15,6"/18,5")/ 1920 x 1080 (21,5")
- Backlight: 250 xd/m2
- Memory: 160 GB HDD
- Working Memory: 2GB (max. 4GB), 2GB (max. 8GB) (21,5")
- Connections:
 - 1 x RJ-45 10/100/1000 Base-T Ethernet Port,
 - 1 x Mic-in, 1 x Line-out, 1 x Line-in, 1 x Line-out (21,5"),
 - 4 x USB-Port,
 - 4 x COM port RJ 45 (RS-232 x 3, RS-232/485 x 1),
 - 1 x Parallel Port, 1 x PCI express, 1 x mini-PCI,
 - 1 x 2.5" HDD Bay,
- Speaker: 2 x 2 Watt
- Power Supply: 12 V DC (included in delivery)
- Operation system: Windows® 7 Professional
- Control T preinstalled
- Front: Glas, True Flat Resistive Gesture Touch