REMOTE CONTROLS FOR COMFORTABLY CONTROLLING MOTION DETECTORS

LUXOMAT® IR-CdS-T



TECHNICAL DATA

Lithium CR2032 -3 Volt (inclusive) depending on lighting conditions




clouded or dark: 5 to 6 m;

sunshine: 2 to 3 m

L 80 x W 60 x H 8 mm



- Using the LUXOMAT® IR-CdS-T infrared remote control, all settings can be made comfortably from the ground without having the annoyance of setting up ladders. It is suitable for use with the $\textbf{LUXOMAT}^{\text{\tiny{\$}}}$ CdS-T-SM photo electric switch.
- The great variety of programs facilitates adapting the motion detector to all individual wishes at any time – even subsequently.
- As additional feature automatically reading-in the current daylight value is optionally available with the IR-CdS-T.
- The lights can be switched on or off anytime with just a touch of the button. That means it is not necessary to install an additional light switch.
- Comes complete with a practical wall bracket (dimensions (approx.): 63 x 29 x 19 mm).



PROGRAM FUNCTIONS





a b	Programmable Opening and closing – also with parental lock and security against sabotage after setting up	•	Automatic reading and saving of the actual light level
o a	Automatic timer with calender - The correct time and date are default.	•	Permanent tamper protection - Permanent inhibition of the detector; only ON- and OFF function on the remote control possible.
8 8	Adjustment of the time for light "ON"	%	Corrections of summer/winter - The correction of summer and winter time is factory-made activated.
	Adjustment of the time for light "OFF"	RESET	Reset - Resetting of all functions
100 (50 Lux) 20 (2ux)	4 preselected exact switch-on and switch-off values (light values) of the connected lighting - 2 to 100 Lux; anytime alterable by remote control	%	Switch on and off the lighting - Independently from the ambient luminosity and energy saving period

Description	Colour	Part number
LUXOMAT® IR-CdS-T	grey	92368

