LUXOMAT® IR-PD4-GH



■ TECHNICAL DATA

②

Lithium CR2032 -3 Volt (inclusive) depending on lighting conditions

clouded or dark: 5 to 6 m;

sunshine: 2 to 3 m

L80 x W 60 x H 8 mm

(i) PRODUCT INFORMATION

- Using the LUXOMAT® IR-PD4-GH infrared remote control, all settings at the LUXOMAT® PD4-M-1C-GH can be made comfortably from the ground without having the annoyance of setting up ladders.
- The great variety of programs facilitates adapting the motion detector to all individual wishes at any time – even subsequently.
- Additional features like automatically reading-in the current daylight value or the useful 2 sec.-test function are also optionally available with the IR-PD4-GH.
- The lights can be switched on or off anytime with just a touch of the button. That means it is not necessary to install an additional light switch.
- Comes complete with a practical wall bracket (dimensions (approx.): 63 x 29 x 19 mm).

■ PROGRAM FUNCTIONS

80



a b	Programmable Opening and closing – also with parental lock and security against sabotage after setting up	10 to	Preselected switch on times for the lighting (Relay and Channel 1): Impulse and 15 sec. to 30 min.
TEST	Test operation - The surveyed room can be paced out independent of surrounding brightness and can be aligned easily after that.	HA OFF	Change between operation modes semiautomatic / automatic
*	Sun button – preselected light value - Daylight operation	RESET	Reset - Resetting of all functions
(1000) (800) (100)	7 preselected light values for the switch on value of the lighting - 20 to 1000 lux	②	Light ON The light will remain switched on for as long as movements are detected in the areas of coverage. After the last detected motion and after the end of the follow-up time the device returns in the chosen automatic
•	Automatic reading and saving of the actual light level	(t)	Determination of the switch on threshold to attain a calculatory target value

Description	Colour	Part number
LUXOMAT® IR-PD4-GH	grey	92215