

LUXOMAT® PD9-DIGI-FC



For installation in light fittings



"Size comparison"


■ TECHNICAL DATA

- 230V~ ±10%
- 360°
- max. Ø 3.00 m
- IP20 / Class III / CE
- Detector**
Ø 18 x H 26 mm
- Power supply**
L 154 x W 40 x H 30 mm
- 25°C to +50°C
- Housing UV- and shock-resistant Polycarbonate
- Channel 1 (Control the lighting)**
- 1000 W, cosφ = 1;
500 VA, cosφ = 0.5
- 30 sec. - 30 min. or impulse

i PRODUCT INFORMATION


- Mini motion detector **LUXOMAT® PD9-DIGI-FC** designed specifically for installation in light fittings
- One channel to switch the lighting
- In spite of small dimensions it switches all types of light fixtures using high performance relay with in rush current limitation especially for electronic ballasts.
- Visible part of the detector is just Ø 11 x 3 mm
- Extremely small and compact
- Motion-dependent switching only
- No luminosity evaluation
- Install in a hole, approx. Ø 11 mm, in the outer ring of a light fitting
- Follow-up time: Can be adjusted manually on the power component via potentiometer
- **Typical applications:**
For installation in fitted downlights

Detector




11 mm cut-out

Power supply



L 154 x W 40 x H 30 mm

NEW!



Description	Colour	Part number
PD9-DIGI-FC	-	92917

INDOOR MOTION DETECTORS