
# DIMMING WITH 2-CHANNEL-MINI-OCCUPANCY DETECTOR AS MASTER


## (MOTION DETECTOR FOR INSIDE USE)

# **LUXOMAT® PD9-M-DIM+HVAC-FC**



"Size comparison"







#### ■ TECHNICAL DATA



**Detector**Ø 45 x H 28 mm **Power supply**L 154 x W 38 x H 25 mm

-25°C to +50°C

Housing UV- and shock-resistant Polycarbonate

IR-PDim, IR-PD-DIM-Mini

Channel 1 (Control the lighting)
Can only be set via remote control

 $\frac{1}{1}$  2300 W,  $\cos \varphi = 1$ ; 1150 VA,  $\cos \varphi = 0.5$ 

1 min. - 30 min. or impulse

10 - 2000 Lux 1-10 VDC, max. 50 EB's

Channel 2 (Control devices)
Can only be set via remote control


dry contact type NO, 3A, 230 V,  $\cos \varphi = 1$ 

Alarm pulse, pulse or 5 - 120 min.

### (i) PRODUCT INFORMATION

 Remote controllable mini-occupancy detector for inside use LUXOMAT® PD9-M-DIM+HVAC-FC in dimming version as Master version with circular detection area

- An easy and cost effective way to realize a constant light control
- Two switching channels, one to switch the lighting, the second to switch other loads e.g. HVAC by potential free relay of the detector
- 1 dim output with 1-10 VDC interface to control electronic ballasts
- The product is programmed for immediate use
- Function full automatic or semi automatic mode, dimming and switching with the optional infrared remote control
- Special version with spring-clamps for easy and time-saving installation into ceilings or directly built into light fittings
- Typical applications: offices, conference rooms, hospitals, galleries, nursery schools



- 1 Walking towards
- 2 Walking across
- 3 Seated activity

### ACCESSORY (OPTIONAL)



Description	Colour	Part number
PD9-M-DIM+HVAC-FC	white	92973
Accessory (optional)		
LUXOMAT® IR-PDim	grey	92200
LUXOMAT® IR-PD-DIM-Mini	grey	92098
Cover ring for PD9 (35 mm)	white, RAL9010	92238
Cover ring for PD9 (35 mm)	silver, RAL9006	92237
Cover ring for PD9 (35 mm)	anthracite, RAL7021	92235