

Order description	Order number	EAN code
MD-C360i/12 mini opal frosted	EP10426018	4015120426018



Short description:

- Mini motion detector with 360° field of detection for recessed ceiling mounting for demand-responsive lighting control and therefore noticeable energy cost reductions
- With a **range of up to 12 m** in diameter at a recommended installation height of 3 m (maximum height 5 m) for use in large rooms and passageways
- With 16 A high-performance relay (tungsten pre-contact), ideal for switching capacitive loads such as electronic ballasts, parallel-compensated fluorescent lamps, compact fluorescent lamps, energy-saving lamps
- Default settings ensure immediate operability
- Automatic lighting control for use without, or with very little, natural light
- Simple programming using remote control
- Extension of the field of detection with parallel connection of max. 8 detectors
- Small, compact design for an installation hole size of just 25 mm in diameter
- Fixed cable, 60 cm long
- New universal ESYLUX fastening technology for quick installation in suspended ceilings, lights, recessed boxes and cupboards, for example
- Recessed ceiling mounting possible in closed, suspended ceilings with supplied spring clips or clamping ring
- Targeted masking out of areas by means of enclosed lens mask

Technical data:

Mains voltage	230 V AC, 50 - 60 Hz
Approx. power consumption	0.2 W
Viewing distance	360°
Range	approx. 12 m in diameter, at an installation height of 3 m
Setting options	electronically by infrared Mobil-PDi/MDi and Mobil RCi-M remote controls (order separately)
Channel 1	lighting
Contact	make contact/non-floating
Switching capacity	230 V AC, 50 Hz/(16 A relay), 2300 W/10 A (cos phi = 1), 1150 VA/5 A (cos phi = 0.5), capacitive load/electronic ballasts - max. inrush current 450 A/200 µs
No. of switchable electronic ballasts	30 x (1 x 18 W), 20 x (2 x 18 W), 25 x (1 x 36 W), 15 x (2 x 36 W), 20 x (1 x 58 W), 10 x (2 x 58 W)
Switch input 1	yes
Time setting	impulse/approx. 1 - 15 mins.
Light measurement	mixed light
Light value	approx. 5 - 2000 Lux
Permissible ambient temperature	-10 °C...+50 °C
Protection type	IP 55
Protection class	II
Supply line	60 cm, 4 x 1.00 mm ²
Included in delivery	includes lens mask; spring installation clips, clamping installation ring
Test symbol	TÜV Süd
Installation type	recessed ceiling mounting
Housing material	UV-stabilised PE, UV stabilised polycarbonate
Approx. measurements	height 70 mm, Ø 58 mm, installation hole size: Ø 25 mm, installation depth: approx. 42 mm
Colour	opal frosted

Accessories

- EM10016011 - Mobil-RCi-M silver
- EM10425509 - Mobil-PDi/MDi silver/metallic blue
- EM10980701 - RC-filter aluminium appearance
- EP10426391 - Spotlight adapter 51/25 opal frosted

Note: Order remote control separately.

Order description
MD-C360i/12 mini opal frosted


Order number
EP10426018

EAN code
4015120426018




Schaltplan


Bewegungsmelder MD-C360i/8 mini, MD-C360i/12 mini




Standardbetrieb



Parallelschaltung von max. 8
Geräten.



Parallelschaltung mit
Treppenlichtautomat.



Standardbetrieb mit zusätzlicher
Ansteuerung durch Schließ-taster. Bei
Bedarf kann das Licht durch den Taster
manuell ein- bzw. ausgeschaltet werden.

www.esylux.com