

Order description PD-C360/24 Slave white

Order number EP10055386

EAN code 4015120055386















## **Short description:**

- "Slave" presence detector for extending the field of detection of a "master" presence detector with 360° field of detection for ceiling mounting
- With a range of up to 24 m in diameter as a cost-efficient system upgrade with up to 9 further extensions
- Ideal for use in areas with ceilings of up to 10 m, such as sports halls and warehouses
- LED switch-off possible via DIP switches
- Masking of interference sources by reducing sensitivity using DIP switches
- Recessed-mounted device as standard
- Surface mounting or recessed ceiling mounting with accessories
- Easily replaceable/paintable cover and design ring (available in "silver" as an accessory)
- Targeted masking out of areas by means of enclosed lens mask
- "Slave" detector can be connected to the following presence detectors: PD-C360i/8, PD-C360i/8plus, PD-C360i/24plus, PD-C360i/8 DIMplus, PD-C360i/24 DIMplus, PD-C360i/24 DUOplus, PD-C360i/24 Dry, PD-C360i/8 Dali, PD-C360i/24 Dali

## Technical data:

Mains voltage 230 V AC, 50 - 60 Hz Approx. power consumption 0.33 W

Viewing distance 360°

Range approx. 24 m diameter, at an installation height of 3 m

Permissible ambient 0 °C...+50 °C

temperature

Protection type recessed-mounted IP 20, IP 20/IP

54 with surface-mounted box (order separately), recessed ceiling-mounted IP 20 (installation set order separately)

Protection class
Included in delivery
Test symbol
Installation type
Installation typ

Housing material UV stabilised polycarbonate height 46 mm, Ø 108 mm white, similar to RAL 9010

## **Accessories**

- EP10425370 Surface-mounted box-C IP 20 white
- EP10425387 Surface-mounted box-C IP 20 silver
- EP10425431 Cover set-C360/24 silver
- EP10425905 Surface-mounted box-C IP 54 white
- EP10425912 Surface-mounted box-C IP 54 silver
- EP10425929 Ceiling-mounted set-C white



Order description PD-C360/24 Slave white Order number EP10055386

EAN code 4015120055386















